



KRYO™ FORTRESS REFRIGERATION MOTORS AND FAN PACKS



ONE MOTOR PROVIDES VERSATILITY, RELIABILITY, AND EFFICIENCY!

- Dual Voltage, Reversible, Multi-Mount ECM Motor
- Dual Voltage Fan Pack Assembly
- IP66/IP67 Rating (water-tight, dust-tight, submersible)
- Single Speed ECM motor with a 68% efficiency rating



MD5411, MD411S

MOTORS	STOCK NUMBER	WATTS	RPM	VOLTS	AMPS	ROTATION	SHAFT	MOTOR DIMENSION	CROSS REFERENCE*
	MD5411	4-27	1550	90-240	.65-.30	REV	1/4-20	3.61"	10891
	MD5411S	4-20	1550	90-240	.55-.20	REV	1/4-20	3.11"	EC5411E, EC5412E, EC5414E



MD5469

MD5470, MD5471, MD5472

FAN PACKS	STOCK NUMBER	WATTS	RPM	VOLTS	AMPS	ROTATION (OSE)	CFM	MOUNTING B.C.	CROSS REFERENCE*
	MD5469	4-20	1550	90-242	.55-.20	CW	355	9.532"	-
	MD5470	4-20	1550	90-243	.55-.20	CW	355	9.800"	05470, EC5470FP
	MD5471	4-20	1450	90-244	.55-.20	CW	390	9.800"	05471
	MD5472	4-20	1550	90-245	.55-.20	CW	415	9.800"	05472, EC5472FP

* Verify that the motor output, watts and RPM are suitable for the motor to be replaced.

SOLID PARTICLE PROTECTION LEVEL: 6 DEGREE OF PROTECTION: Dust tight - No ingress of dust; complete protection against contact.		LIQUID INGRESS PARTICLE PROTECTION LEVEL: 6 DEGREE OF PROTECTION: Powerful water jets - Water projected in powerful jets against the enclosure from any direction shall have no harmful effects.			SOLID PARTICLE PROTECTION LEVEL: 6 DEGREE OF PROTECTION: Dust tight - No ingress of dust; complete protection against contact.		LIQUID INGRESS PARTICLE PROTECTION LEVEL: 7 DEGREE OF PROTECTION: Immersion - Ingress of water in harmful quantity shall not be possible when the enclosure is immersed in water under defined conditions of pressure and time.	
--	--	--	--	--	--	--	---	--

1325 Heil Quaker Blvd • LaVergne, TN 37086 • PH: 800-672-6495 • FAX: 800-468-2062

www.genteqmotors.com

